

25 GHz Picosecond Fiber Laser



Applications

- 100 GHz Ethernet
- Optical clock for 25, 50, 100, 200 GHz OTDM system
- Transmission network characterization
- Spectral comb
- High speed O/E conversion
- Optical sampling
- Metrology

Features

- Repetition rate continuously tunable from 22 to 28 GHz
- Wavelength tunable from 1530 to 1565 nm
- Pulse width selectable from 1.5 to 10 ps
- Average output power greater than 20 mW
- Transform-limited output
- Linearly polarized output
- Minimal pulse pedestal
- Low timing jitter
- Optional automatic mode-locking

The C-band 25 GHz picosecond fiber laser (PSL-25) is an actively mode-locked fiber laser with repetition rate from 22 to 28 GHz that provides a stable and reliable optical clock with turnkey operation, specially designed for 100 GHz Ethernet applications. A 100 GHz pulse rate is achieved by using the PSL-25 in conjunction with Calmar's Bit Rate Multiplier (BRM-T4). Along with a portable design, the PSL-25 series offers user-friendly front panel control knobs for flexible adjustment of wavelength and output power. The wavelength can be tuned throughout the C-band. The pulse width is factory selectable from 1.5 to 10 ps, with transform-limited spectral width and a better than -20 dB pedestal. The timing jitter is as low as 50 fs and the side mode suppression is better than -75 dB. An output power of greater than 20 mW obviates the need for an additional optical amplification stage. Options for 780 nm or 1 μ m band are also available.

HIGH REPETITION RATE PICOSECOND FIBER LASER

Technical Specifications

Model Number	PSL-25-1T	PSL-25-2T
Pulse Width (ps)*	<1.5	<2.0
Output Wavelength (nm)**	1530 ~ 1565 (tunable)	
Repetition Rate (GHz)	22 ~ 28 (tunable)	
Timing Jitter (fs)	<50 (carrier offset 100 Hz ~ 1 MHz)	
Amplitude Noise (%)	<1	
Output Power (mW)	>20	
Operating Temp (°C)	15 ~ 30	
Operating Voltage (VAC)	85 ~ 264	
Dimensions (cm)	48(w) x 42(d) x 9(h)	

* Pulse width is selectable within 1.5 to 10 ps. A sech^2 pulse shape (convolution factor of 0.65) is used to determine the pulse width for the second harmonic autocorrelation trace.

** 780 nm or 1 μm band is available.

Due to our continuous improvement program, specifications are subject to change without notice.

